








tamko.com











# RESIDENTIAL ROOFING PRODUCT GUIDE



## SHINGLES / LAMINATED

DESIGN	TAMKO PRODUCT	SPECIFICATIONS	LIMITED WARRANTY	CERTIFICATIONS	U.L.	PRODUCTION LOCATION
 <ul style="list-style-type: none"> <li>Laminated</li> <li>Metric Size</li> <li>Algae Relief</li> <li>Shadowtone</li> <li>Choose From Classic &amp; ANC Colors</li> </ul>	<b>HERITAGE®</b>	13-1/4" x 39-3/8" 5-5/8" Exposure 64 Shingles per Sales Square 3 Bundles per Sales Square 98.4 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>30-yr Limited Warranty</li> <li>15-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/ high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph) ICC-ES ESR-1501 (Dallas only)	U.L. Listed for Class A Fire Resistance and Wind Resistance	Joplin Frederick Phillipsburg Tuscaloosa* Dallas***
	<b>HERITAGE® IR</b>	13-1/4" x 39-3/8" 5-5/8" Exposure 64 Shingles per Sales Square 3 Bundles per Sales Square 98.4 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>30-yr Limited Warranty</li> <li>15-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/ high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph) ICC-ES ESR-1501 U.L. 2218, Class 4	U.L. Listed for Class A Fire Resistance, Wind Resistance and Class 4 Impact Resistance**	Dallas
	<b>HERITAGE® PREMIUM</b>	13-1/4" x 39-3/8" 5-5/8" Exposure 64 Shingles per Sales Square 3 Bundles per Sales Square 98.4 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>50-yr Limited Warranty</li> <li>20-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/ high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph) ICC-ES ESR-150(Dallas and Phillipsburg only)	U.L. Listed for Class A Fire Resistance and Wind Resistance	Phillipsburg Tuscaloosa* Dallas***
 <ul style="list-style-type: none"> <li>Laminated</li> <li>Metric Size</li> <li>Algae Relief</li> <li>Shadowtone</li> <li>Choose From Six Heritage Woodgate Colors</li> </ul>	<b>HERITAGE WOODGATE®</b>	13-1/4" x 39-3/8" 5-5/8" Exposure 64 Shingles per Sales Square 3 Bundles per Sales Square 98.4 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>30-yr. Limited Warranty</li> <li>15-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/ high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph) ICC-ES ESR-1501	U.L. Listed for Class A Fire Resistance and Wind Resistance	Dallas***
 <ul style="list-style-type: none"> <li>Laminated</li> <li>Standard Size</li> <li>Algae Relief</li> <li>Shadowtone</li> <li>Choose From Classic and ANC Colors</li> </ul>	<b>HERITAGE®</b>	12" x 36-3/8" 5" Exposure 78 Shingles per Sales Square 3 Bundles per Sales Square 98.5 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>30-yr. Limited Warranty</li> <li>15-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/ high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph)	U.L. Listed for Class A Fire Resistance and Wind Resistance	Frederick**
	<b>HERITAGE® PREMIUM</b>	12" x 36" 5" Exposure 80 Shingles per Sales Square 4 Bundles per Sales Square 100.0 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>50-yr. Limited Warranty</li> <li>20-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/ high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph)	U.L. Listed for Class A Fire Resistance and Wind Resistance	Frederick**
 <ul style="list-style-type: none"> <li>Laminated</li> <li>Standard Size</li> <li>Algae Relief</li> <li>Shadowtone</li> <li>Choose From Six Heritage Woodgate Colors</li> </ul>	<b>HERITAGE WOODGATE®</b>	12" x 36-3/8" 5" Exposure 78 Shingles per Sales Square 3 Bundles per Sales Square 98.5 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>30-yr. Limited Warranty</li> <li>15-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/ high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462	U.L. Listed for Class A Fire Resistance and Wind Resistance	Frederick**
 <ul style="list-style-type: none"> <li>Laminated</li> <li>Premium Cut</li> <li>Shake Look</li> <li>Algae Relief</li> <li>Choose From Five Heritage Vintage Colors</li> </ul>	<b>HERITAGE® VINTAGE®</b>	17-1/2" x 40" 5" Exposure 72 Shingles per Sales Square 6 Bundles per Sales Square 100.0 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>50-yr. Limited Warranty</li> <li>20-yr. FULL START</li> <li>5-yr. Limited Transferability</li> <li>10-yr. Algae Relief Algae Cleaning Limited Warranty</li> <li>15-yr. Limited Warranty on winds up to 110 mph or 130 mph w/high wind application</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph) ICC-ES ESR-1501	U.L. Listed for Class A Fire Resistance and Wind Resistance	Phillipsburg****



DESIGN	TAMKO PRODUCT	SPECIFICATIONS	LIMITED WARRANTY	CERTIFICATIONS	U.L.	PRODUCTION LOCATION
 <ul style="list-style-type: none"> <li>• 3-Tab</li> <li>• Standard Size</li> <li>• Algae Relief</li> </ul>	<b>ELITE GLASS-SEAL®</b>	12-1/4" x 36" 5-1/8" Exposure 78 Shingles per Sales Square 3 Bundles per Sales Square 100.0 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>• <b>25-yr Limited Warranty</b></li> <li>• 5-yr. FULL START</li> <li>• 2-yr. Limited Transferability</li> <li>• 10-yr. Algae Relief</li> <li>• Algae Cleaning Limited Warranty</li> <li>• 5-yr. Limited Warranty on winds up to 60 mph</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381, Class H (150 mph) ICC-ES ESR - 1501 (Joplin only)	U.L. Listed for Class A Fire Resistance and Wind Resistance	Joplin Frederick** Tuscaloosa*
	<b>TAMKO GLASS-SEAL®</b>	12-1/4" x 36" 5-1/8" Exposure 78 Shingles per Sales Square 3 Bundles per Sales Square 100.0 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>• <b>20-yr Limited Warranty</b></li> <li>• 3-yr. FULL START</li> <li>• 2-yr. Limited Transferability</li> <li>• 10-yr. Algae Relief</li> <li>• Algae Cleaning Limited Warranty</li> <li>• 5-yr. Limited Warranty on winds up to 60 mph</li> </ul>	ASTM D3161, Type I, Class F (110 mph) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381 Class H (150 mph)	U.L. Listed for Class A Fire Resistance and Wind Resistance	Tuscaloosa*
 <ul style="list-style-type: none"> <li>• 3-Tab</li> <li>• Standard Size</li> </ul>	<b>TAMKO GLASS SEAL®</b>	12-1/4" x 36" 5-1/8" Exposure 78 Shingles per Sales Square 3 Bundles per Sales Square 100.0 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>• <b>20-yr Limited Warranty</b></li> <li>• 3-yr. FULL START</li> <li>• 2-yr. Limited Transferability</li> <li>• 5-yr. Limited Warranty on winds up to 60 mph</li> </ul>	ASTM D3161, Type I, Class F (110 mph), (Frederick) ASTM D3161, Type I, Class A (60mph) (Joplin) ASTM E108, Class A ASTM D3462 ASTM D 7158, Class H (150 mph) U.L. 2390/ASTM D 6381 Class H (150 mph)	U.L. Listed for Class A Fire Resistance and Wind Resistance	Frederick Joplin
 <ul style="list-style-type: none"> <li>• Hip and Ridge</li> <li>• Standard Size</li> <li>• Algae Relief</li> </ul>	<b>12-1/4" x 12" HIP &amp; RIDGE</b>	12-1/4" x 12" <sup>†</sup> 5-1/8" Exposure 234 Shingles per 100 lin. ft. 3 Bundles per 100 lin. ft.	-	ASTM D3161, Type I, Class F (110 mph), ASTM E108, Class A ASTM D 3462	U.L. Listed for Class A Fire Resistance and Wind Resistance	Joplin <sup>††</sup> Frederick <sup>†</sup>
 <ul style="list-style-type: none"> <li>• Hip and Ridge</li> <li>• Standard Size</li> <li>• Algae Relief</li> </ul>	<b>HERITAGE® VINTAGE® 12" x 12" HIP &amp; RIDGE</b>	12" x 12" 5" Exposure 240 Shingles per 100 lin. ft. 4 Bundles per 100 lin. ft.	-	-	N/A	Phillipsburg
 <ul style="list-style-type: none"> <li>• Pre-cut Starter</li> <li>• Faster install time</li> <li>• Algae Relief</li> </ul>	<b>HERITAGE® VINTAGE® STARTER</b>	12-1/2" x 36" 20 Shingles per bundle 60 lin. ft. coverage per bundle	-	-	N/A	Phillipsburg
 <ul style="list-style-type: none"> <li>• Pre-cut Starter</li> <li>• Faster install time</li> </ul>	<b>TAMKO® SHINGLE STARTER</b>	7" x 36" 34 Shingles per bundle 102 lin. ft. coverage per bundle	-	-	N/A	Joplin Frederick Tuscaloosa
 <ul style="list-style-type: none"> <li>• Pre-cut Starter</li> <li>• Faster install time</li> </ul>	<b>TAMKO® 10 INCH STARTER</b>	10" x 40" 30 Shingles per bundle 100 lin. ft. coverage per bundle	-	-	N/A	Phillipsburg

† Frederick produced 12-1/4" x 12" Hip & Ridge is approved by Miami Dade County Florida NOA: 11-0913.11 Expiration Date 01/08/14

†† Joplin produced 12-1/4" x 12" Hip & Ridge is approved by Miami Dade County Florida NOA:11-0913.11 Expiration Date 01/08/14.

\* Tuscaloosa produced Glass-Seal, Elite Glass-Seal, Heritage and Heritage Premium meet Florida Building Code, Miami-Dade County Florida NOA 11-0913.12, Expiration Date: 4/11/17; NOA 11-0223.11, Expiration Date: 12/01/17 and TAS 100-95 wind and wind driven rain.







\*\* Frederick produced Elite Glass-Seal, Heritage (Standard Size), Heritage Woodgate and Heritage Premium meet Florida Building Code, Miami-Dade County Florida NOA.: 11-0913.12 Expiration Date: 04/11/17; NOA 11-1228.01 Expiration Date 03/21/17 and TAS 100-95 wind and wind driven rain.

\*\*\* Dallas produced Heritage and Heritage Premium meet Florida Building Code, Miami-Dade County Florida NOA: 11-0223.11 Expiration Date:12/01/15 and TAS 100-95 wind and wind driven rain. Dallas produced Heritage Woodgate shingles meet Florida Building Code, Miami-Dade County Florida NOA: 11-0223.11 Expiration Date: 12/01/15


\*\*\*\* Phillipsburg produced Heritage Vintage meets Florida Building Codes, Miami Dade County Florida NOA: 11-0720.03 Expiration Date: 11/23/16 and TAS 100-95 wind and wind driven rain.

\*\* Compliance testing for U.L. 2218 Class 4 impact resistance occurs in a laboratory setting and may not be equivalent to real-world exposure to weathering conditions, including hail storms. TAMKO does not warrant against damage by hail. See TAMKO's Limited Warranty for complete details.




DESIGN	TAMKO PRODUCT	SPECIFICATIONS	LIMITED WARRANTY	CERTIFICATIONS	U.L.	PRODUCTION LOCATION
 • Steel • Wood Look • Choose from Eight Cool Colors	<b>METALWORKS® ASTONWOOD®</b>	12-5/8" x 39-3/4" 12" Exposure 30 Shingles per Sales Square 1 Box per Sales Square Nominal 0.0135" Thickness 98.4 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>• 50-yr Limited Warranty</li> <li>• 25-yr. FULL START</li> <li>• Limited Transferability</li> <li>• 50-yr. Limited Warranty on winds up to 110 mph</li> <li>• 30-yr. Finish Limited Warranty</li> </ul>	ASTM D3161, Class F (110 MPH) ICC-ES ESR-1129 CCMC 13011-R MEA 1-56-00-M Vol. II 	U.L. Listed for Class A Fire Resistance; Wind Resistance; Class 4 Impact Resistance	Joplin
 • Steel • Slate Look • Choose from Four Cool Colors	<b>METALWORKS® STONECREST® SLATE</b>	12-5/8" x 39-3/4" 12" Exposure 30 Shingles per Sales Square 2 Boxes per Sales Square Nominal 0.0162" Thickness 98.4 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>• 50-yr Limited Warranty</li> <li>• 25-yr. FULL START</li> <li>• Limited Transferability</li> <li>• 50-yr. Limited Warranty on winds up to 110 mph</li> <li>• 30-yr. Finish Limited Warranty</li> </ul>	ASTM D3161, Class F (110 MPH) ICC-ES ESR-1129 CCMC 13011-R MEA 1-56-00-M Vol. II 	U.L. Listed for Class A Fire Resistance; Wind Resistance; Class 4 Impact Resistance	Joplin
 • Steel • Tile Look • Choose from Three Cool Colors	<b>METALWORKS® STONECREST® TILE</b>	12-5/8" x 39-3/4" 12" Exposure 30 Shingles per Sales Square 2 Boxes per Sales Square Nominal 0.0162" Thickness 98.4 sq. ft. Coverage per Sales Square	<ul style="list-style-type: none"> <li>• 50-yr Limited Warranty</li> <li>• 25-yr. FULL START</li> <li>• Limited Transferability</li> <li>• 50-yr. Limited Warranty on winds up to 110 mph</li> <li>• 30-yr. Finish Limited Warranty</li> </ul>	ASTM D3161, Class F (110 MPH) ICC-ES ESR-1129 CCMC 13011-R MEA 1-56-00-M Vol. II 	U.L. Listed for Class A Fire Resistance; Wind Resistance; Class 4 Impact Resistance	Joplin
<ul style="list-style-type: none"> <li>• Ridge Cap</li> <li>• Hip Cap Tapered</li> <li>• Starter</li> <li>• Gable</li> <li>• Valley</li> <li>• J-Channel</li> <li>• Screws</li> <li>• Sidewall</li> <li>• Clips</li> <li>• Trim Coil</li> <li>• Snow Guards</li> <li>• Touch up Paint</li> <li>• Hip &amp; Ridge Seal</li> </ul>	<b>METALWORKS® METAL &amp; NON-METAL ACCESSORIES</b>	Varies - See items listed below and website for more details	<ul style="list-style-type: none"> <li>• 50-yr Limited Warranty</li> <li>• 25-yr. FULL START</li> <li>• Limited Transferability</li> <li>• 50-yr. Limited Warranty on winds up to 110 mph</li> <li>• 30-yr. Finish Limited Warranty on metal accessories</li> </ul>	—	N/A	Joplin


**METAL ACCESSORIES** (Accessories lbs as packaged weight) All values stated as nominal.




**Starter**  
10 pc/ctn. - 100 lf/ctn.  
35 lbs/ctn.  
30 ctn./pallet




**Gable**  
10 pc/ctn. - 100 lf/ctn.  
41 lbs/ctn.  
24 ctn./pallet




**Valley**  
5 pc/ctn. - 50 lf/ctn.  
56 lbs/ctn.  
12 ctn./pallet



**J-Channel**  
10 pc/ctn. - 100 lf/ctn.  
17 lbs/ctn.  
30 ctn./pallet



**Sidewall**  
5 pc/ctn. - 50 lf/ctn.  
25 lbs/ctn.  
30 ctn./pallet



**Colored Screws**  
50 pc/bag  
0.5 lbs/bag




**Hip Cap Tapered  
StoneCrest or AstonWood**  
50 pc/ctn. - 50 lf/ctn.  
21 lbs/ctn.  
32 ctn./pallet



**12" Ridge Cap**  
25 pc/ctn. - 25 lf/ctn.  
19 lbs/ctn.  
45 ctn./pallet



**Clips**  
400 pc/ctn. - 100+/- pc/sq.  
8 lbs/ctn.  
90 ctn./pallet



**Snow Guard**  
100 pc/ctn.  
16 lbs/ctn.  
30 ctn./pallet



**Trim Coil**  
22-1/4" x 50'  
1 pc/ctn.  
47 lbs/ctn.  
30 ctn./pallet

**NON-METAL ACCESSORIES**



**Touch Up Paint**  
2 oz/btl.  
12 btl/ctn.  
2.2 lbs/ctn.



**Hip & Ridge Seal**  
4" x 50'  
1 pc/ctn.  
6 lbs/ctn.

TAMKO PRODUCT	DESCRIPTION	SPECIFICATIONS	APPLICATION METHOD	CERTIFICATIONS
<b>TAMKO® ROLL VENT®</b> Continuous Ridge Vent	A self-contained ridge vent product on a roll. Lightweight, compression resistant shingle-over ventilation. Provides 18 sq. inches of net free area per linear foot.	10.5" x 20', 5 rolls per bag, 100 ft. per bag 10.5" x 50', 2 rolls per box, 100 ft. per box	Fasten with nails provided with product. Install along with an equal or greater amount of soffit ventilation.	Florida Building Code
<b>TAMKO® RAPID RIDGE®</b> Nail Gunable Ridge Vent	A nail-gun version of TAMKO Roll Vent self-contained ridge vent product on a roll. Provides 12.5 sq. inches of net free area per linear foot.	10.5" x 20', 5 rolls per bag, 100 ft. per bag 10.5" x 50', 2 rolls per box, 100 ft. per box	Fasten with nails provided with product and nail gun. Install along with an equal or greater amount of soffit ventilation.	Florida Building Code
<b>COOLRIDGE®</b> Sectional Ridge Vent	A self-contained sectional ridge vent product. Provides 18 sq. inches of net free area per linear foot.	14-3/4" x 48", 12 pieces per bundle, 48 ft. per bundle	Fasten with nails provided with product. Install along with an equal or greater amount of soffit ventilation	Florida Building Code
<b>COOLRIDGE®</b> Sectional Ridge Vent with Filter	A self-contained sectional ridge vent product with a filter designed to protect against weather infiltration. Provides 18 sq. inches of net free area per linear foot.	14-3/4" x 48", 12 pieces per bundle, 48 ft. per bundle	Fasten with nails provided with product. Install along with an equal or greater amount of soffit ventilation	-
<b>XTRACTOR VENT® XLP TURBO</b> Nail Gunable Continuous Ridge Vent	A nail-gunable, externally baffled ridge vent product. Provides 12.75 sq. inches of net free area per linear foot.	14" x 25', 1 roll per bundle, 25 ft. per bundle	Fasten with nails provided with product and nail gun. Install along with an equal or greater amount of soffit ventilation.	Florida Building Code
<b>TAMKO® SOLAR ATTIC VENT</b> Surface Mount	A low-profile ventilator in a square design that mounts to the roof surface to integrate with shingles and the shape of the roof to combine the beauty of a single unobtrusive unit with the benefits of a solar-powered ventilator system.	25" x 21-3/4" x 7-1/2", (Vent dimensions) 25-1/2" x 22", (Base Flange dimensions) 1 each per carton 24 cartons per pallet	Fasten with nails. Install along with soffit ventilation, minimum open air inlet of 4.25 sq. ft. required.	-
<b>TAMKO® SOLAR ATTIC VENT</b> Curb Mount	A low-profile ventilator in a square design that mounts to a fabricated curb box frame on flat, tiled, or unusually steep sloped roof installations to combine the beauty of a single unobtrusive unit with the benefits of a solar-powered ventilator system.	25" x 21-3/4" x 8-3/4", (Vent dimensions) 19-3/4" x 16-1/2", (Base Flange dimensions) 1 each per carton 24 cartons per pallet	Fasten with nails. Install along with soffit ventilation, minimum open air inlet of 4.25 sq. ft. required.	-
<b>TAMKO® SOLAR ATTIC VENT</b> Remote Mount	A low-profile ventilator in a square design that mounts to the roof surface in a two-piece system with the ventilator to be installed independently of the solar panel for less visibility and with the solar panel positioned to best capture solar energy.	25" x 21-3/4" x 7-1/2", (Vent dimensions) 25-1/2" x 22", (Vent Base Flange dimensions) 25" x 21-3/4" x 3/4", (Solar Panel dimensions) 1 each per carton 24 cartons per pallet	Fasten with nails. Install along with soffit ventilation, minimum open air inlet of 4.25 sq. ft. required.	-
<b>TAMKO® SOLAR ATTIC VENT</b> Gable Mount	A low-profile ventilator in a square design that mounts inside the attic space directly behind the gable vent when roof mounting is not possible or desirable. Unit includes a remote-mounted flat solar panel for positioning to best capture solar energy.	19-3/4" x 16-1/2" x 8-3/4", (Vent dimensions) 25" x 21-3/4" x 3/4" (Solar Panel dimensions) 1 each per carton 24 cartons per pallet	Fasten with nails. Install along with soffit ventilation, minimum open air inlet of 4.25 sq. ft. required.	-
<b>TAMKO® SOLAR ATTIC VENT</b> Cold-Weather Thermostat	An Optional Solar Attic Vent accessory designed to disengage the fan of the attic vent when the temperature drops below 50°F.	-	Follow wiring instructions included with unit.	-



<b>TAMKO PRODUCT</b>	<b>DESCRIPTION</b>	<b>SPECIFICATIONS</b>	<b>APPLICATION METHOD</b>	<b>CERTIFICATIONS</b>	<b>PRODUCTION LOCATION</b>
<b>MOISTURE GUARD PLUS®</b> Ice & Rain Protective Underlayment	Self-adhering SBS modified sheet for prevention of water penetration caused by wind-blown rain or ice damming. Use at rakes, eaves, valleys, or over the entire deck with proper ventilation.	1 Square: 39-3/8" x 30'6" (100 sq. ft.) 42 rolls per pallet, (Joplin only) 1.5 Square: 39-3/8" x 45'-8" (150 sq. ft.) 30 rolls per pallet, (Joplin only) 2 Square: 39-3/8" x 61' (200 sq. ft.) 24 rolls per pallet, Thickness: 55 mils.	Self-adhering	ASTM D1970 ICC-ES ESR-1252 U.L. Prepared Roofing Accessory Label Florida Building Code	Joplin Naples
<b>TW-METAL &amp; TILE</b> Underlayment	A flexible, fiberglass reinforced, self-adhering rubberized asphalt sheet membrane with a polymer film on the surface and a split treated release film on the adhesive side.	2 Square: 39-3/8" x 61' (200 sq. ft.) 20 rolls per pallet, Thickness: 75 mils.	Self-adhering	ASTM D1970 (Joplin only) ICC-ES ESR-2531 Florida Building Code	Joplin Naples
<b>TW UNDERLAYMENT</b>	Self-adhering, rubberized asphalt with textured polymer surface for skid resistance and a treated release film.	2 Square: 39-3/8" x 61" (200 sq. ft.) 24 rolls per pallet, Thickness: 40 mils.	Self-adhering	ICC-ES ESR-1252 Florida Building Code Miami-Dade County Approved	Columbus
<b>TAM-SHIELD® SYNTHETIC UNDERLAYMENT</b>	A high strength woven polypropylene synthetic roof underlayment formulated with a polymeric surface coating that imparts skid resistance.	10 square: 48" x 250' (1000 sq. ft.) 30 rolls per pallet 5 square: 48" x 125' (500 sq. ft.) 48 rolls per pallet, Thickness: 6 mils.	Mechanically Fastened	U.L. Prepared Roofing Accessory Label Miami-Dade County, FL NOA 11-0520.04 Expiration Date: 10/04/2015 ICC-ES ESR-3237 Florida Building Code	-
<b>SLATE-SURFACED</b> Roll Roofing	An organic based product, saturated with hot asphalt, coated on both sides with weathering grade asphalt and surfaced with mineral granules.	36" x 36', 1 square 25 rolls per pallet	Apply using nails and TAMKO Cold Method and Lap Cement or TAMKO Plastic Roof Cement	-	Joplin Green Cove Springs
<b>ASTM SLATE SURFACED</b> Roll Roofing	An organic based product, saturated with hot asphalt, coated on both sides with weathering grade asphalt and surfaced with mineral granules.	36" x 36', 1 square. 25 rolls per pallet	Apply using nails and TAMKO Cold Method and Lap Cement or TAMKO Plastic Roof Cement	ASTM D6380, Class M, Type II ASTM D249, Type II U.L. Prepared Roofing Accessory Label Florida Building Code	Green Cove Springs
<b>4" SELVEDGE EDGE</b> Roll Roofing	Constructed like the slate surfaced roll product, with a 4" selvedge edge and a 32" surface of mineral granules.	36" x 36', 1 square. 25 rolls per pallet	Apply using nails and TAMKO Cold Method and Lap Cement or TAMKO Plastic Roof Cement		Green Cove Springs
<b>SA CAP</b> Roll Roofing	A self-adhering SBS-modified cap sheet with a 180 gram polyester mat, coated with SBS-modified asphalt and surfaced with mineral granules.	33'-6-1/4" x 39-3/8', 17" exposure, 1 square. 20 rolls per pallet	Self-adhering	U.L. Classified Membrane ASTM D6164, Type I, G Florida Building Code	Joplin
<b>TAMKO SA BASE</b>	A self-adhering SBS-modified base sheet with a fiberglass mat, coated with SBS-modified asphalt and a polymer film surface.	65'-10" x 39-3/8', 2 square, 20 rolls per pallet	Self-adhering or Mechanically Fastened	U.L. Classified Base Sheet ASTM D1970 Florida Building Code	Joplin
<b>AWAPLAN PREMIUM</b>	SBS-modified cap sheet with a 250 gram polyester mat, coated with SBS-modified asphalt and surfaced with mineral granules.	33'-5" x 39-3/8", 1 square 20 rolls per pallet	TAMKO M3 Adhesive or TAM-PRO 856 Premium SBS Adhesive or Hot Mop	U.L. Classified Membrane ASTM D6164, Type II ICC-ES ESR-1013 Miami-Dade County Approved Florida Building Code	Joplin
<b>AWAPLAN 170</b>	Middle-weight SBS-modified cap sheet with a 180 gram polyester mat, coated with SBS-modified asphalt and surfaced with mineral granules.	33'-5" x 39-3/8", 1 square 20 rolls per pallet	TAMKO M3 Adhesive or TAM-PRO 856 Premium SBS Adhesive or Hot Mop	U.L. Classified Membrane ASTM D6164, Type II ICC-ES ESR-1013 Miami-Dade County Approved Florida Building Code	Joplin
<b>AWAFLEX®</b>	An SBS-modified cap sheet with a 155 gram polyester mat, coated with SBS-modified asphalt and surfaced with mineral granules.	32'-6" x 39-3/8", 1 square 20 rolls per pallet	TAMKO M3 Adhesive or TAM-PRO 856 Premium SBS Adhesive or Hot Mop	U.L. Classified Membrane Miami-Dade County Approved Florida Building Code	Joplin
<b>TYPE 43 ORGANIC BASE SHEET</b>	A quality organic base sheet used as a nailed base ply in AWAPLAN and AWAFLEX modified roofing applications.	72" x 36', 2 square (216 sq. ft.) 20 rolls per pallet	Mechanically Fastened	U.L. Type 15 ASTM D 2626 Miami-Dade County Approved Florida Building Code	Joplin, Green Cove Springs

**UNDERLAYMENTS, FELTS & ROLL ROOFING (continued)**

<b>TAMKO PRODUCT</b>	<b>DESCRIPTION</b>	<b>SPECIFICATIONS</b>	<b>APPLICATION METHOD</b>	<b>CERTIFICATIONS</b>	<b>PRODUCTION LOCATION</b>
<b>NO. 15 U.L. Felt</b>	U.L. organic felt used as an underlayment under asphalt shingles.	36" x 144', 4 square (432 sq. ft.) Laying lines 2", 4", 17" 20 rolls per pallet	Mechanically Fastened	ASTM D226, Type I U.L. Built-Up Type 15 Label Florida Building Code	Joplin, Frederick, Tuscaloosa
<b>NO. 15 ASTM D4869 Felt</b>	ASTM D4869 organic felt used as an underlayment under asphalt shingles.	36" x 144', 4 square (432 sq. ft.) Laying lines 2", 4", 17" 30 rolls per pallet (Tuscaloosa, Green Cove Springs) 25 rolls per pallet (Phillipsburg) 20 rolls per pallet (Frederick)	Mechanically Fastened	ASTM D4869, Type I U.L. Prepared Roofing Accessory Label Florida Building Code	Phillipsburg, Green Cove Springs, Frederick, Tuscaloosa
<b>NO. 15 ASTM Felt</b>	ASTM organic felt used as an underlayment under asphalt shingles.	36" x 144', 4 square (432 sq. ft.) Laying lines 2", 4", 17" 25 rolls per pallet (Phillipsburg) 20 rolls per pallet (Green Cove Springs)	Mechanically Fastened	ASTM D226, Type I Florida Building Code	Phillipsburg, Green Cove Springs
<b>NO. 15 Felt</b>	Tough TAMKO organic felt used as an underlayment under asphalt shingles.	36" x 144', 4 square (432 sq. ft.) Laying lines 2", 4", 17" 30 rolls per pallet	Mechanically Fastened	U.L. Prepared Roofing Accessory Label	Joplin, Frederick, Phillipsburg, Tuscaloosa
<b>NO. 30 U.L. Felt</b>	U.L. organic felt used as an underlayment under asphalt shingles.	36" x 72', 2 square (216 sq. ft.) Laying lines 2", 4", 17" 20 rolls per pallet	Mechanically Fastened	ASTM D226, Type II U.L. Built-Up Type 30 Label Florida Building Code	Joplin, Frederick, Tuscaloosa, Green Cove Springs
<b>NO. 30 ASTM Felt</b>	ASTM organic felt used as an underlayment under asphalt shingles.	36" x 72', 2 square (216 sq. ft.) Laying lines 2", 4", 17" 20 rolls per pallet	Mechanically Fastened	ASTM D226, Type II U.L. Prepared Roofing Accessory (Green Cove Springs only) Florida Building Code	Phillipsburg, Green Cove Springs
<b>NO. 30 ASTM D4869 Felt</b>	ASTM D4869 organic felt used as an underlayment under asphalt shingles.	36" x 72', 2 square (216 sq. ft.) Laying lines 2", 4", 17" 42 rolls per pallet (Frederick, Green Cove Springs) 30 rolls per pallet (Joplin, Phillipsburg, Tuscaloosa)	Mechanically Fastened	ASTM D4869, Type III (Phillipsburg) and Type 1 (All locations) U.L. Prepared Roofing Accessory Label Florida Building Code	Phillipsburg, Green Cove Springs, Tuscaloosa, Joplin, Frederick
<b>NO. 30 Felt</b>	Tough non-perforated organic felt used as an underlayment under shingles.	36" x 72', 2 square (216 sq. ft.) Laying lines 2", 4", 17" 30 rolls per pallet	Mechanically Fastened	U.L. Prepared Roofing Accessory Label	Joplin, Frederick, Phillipsburg, Tuscaloosa
<b>NO. 30 ASTM Shake Underlayment</b>	Organic felt used as an underlayment under wood shake shingles and asphalt shingles.	18" x 120', 1.667 squares (180 sq. ft.) Laying lines 8" & 10" 24 rolls per pallet	Mechanically Fastened	ASTM D226, Type II	Joplin
<b>Sat. Felt No. 30 18"</b>	Organic felt used as an underlayment under wood shake shingles.	18" x 72' 1 square (108 sq. ft.) Laying line 8" & 10" 60 rolls per pallet	Mechanically Fastened	—	Joplin, Phillipsburg
<b>SHAKE UNDERLAYMENT</b>	Organic felt used as an underlayment under wood shake shingles.	18" x 120', 1.667 squares (180 sq. ft.) Laying lines 8" & 10" 40 rolls per pallet	Mechanically Fastened	—	Joplin
<b>ASTM TILE UNDERLAYMENT</b>	ASTM organic felt, surfaced with opaque granules, used as an underlayment for concrete tile.	36" x 36', 1 square (108 sq. ft.) 25 rolls per pallet	Mechanically Fastened	ASTM D6380, Class M, Type II ASTM D249, Type II U.L. Prepared Roofing Accessory Florida Building Code	Green Cove Springs
<b>MASTER SMOOTH</b>	An organic based product, saturated with asphalt, coated on both sides with weathering grade asphalt and surfaced with a fine mineral surface.	36" x 36', 1 square (108 sq. ft.) 30 rolls per pallet	Mechanically Fastened	ASTM D6380, Class S, Type IV (replaces ASTM D224, Type I) U.L. Prepared Roofing Accessory Label Florida Building Code	Joplin



- 1** Cements and Sealants
- 2** Underlayments
- 3** Ventilation
- 4** Ice and Rain Protective Underlayments
- 5** Shingle Starter
- 6** Hip & Ridge Shingles
- 7** Heritage® Shingle Options

## Be sure your roof is protected in these critical areas.

Your roof consists of much more than just shingles. Underneath are several additional products all working to help protect your home from the elements. Choosing TAMKO® products will provide professional-grade performance to enhance roof protection and durability.

## Building products for the professional.



Since 1944, building professionals and homeowners have looked to TAMKO® for quality products built to perform. Our residential line also features Heritage® Vintage® Laminated Asphalt Shingles, Heritage® Premium and Heritage® Laminated Asphalt Shingles, Heritage® Woodgate® Laminated Asphalt Shingles, MetalWorks® Steel Shingles and 3-tab shingles. Additional residential offerings include EverGrain® and EverGrain® Envision® Composite Decking, Elements® DockBoard, Marquee® Railing System, Tam-Rail® Railing System, waterproofing materials, ventilation products and asbestos-free cements and coatings. Each of these products delivers TAMKO quality, performance and durability.



® P.O. Box 1404  
 Joplin, MO 64802-1404  
 1-800-641-4691  
 tamko.com

Information included in this brochure was current at the time of printing. To obtain a copy of the most current version of this brochure or TAMKO's Limited Warranties, visit us online at [tamko.com](http://tamko.com) or call us at 800-641-4691.

©2013 TAMKO Building Products, Inc.  
 TAMKO, AstonWood, AwaFlex, CoolRidge, Elite Glass-Seal, EverGrain, Envision, Elements, Tam-Rail, Heritage, MetalWorks, Moisture Guard Plus, StoneCrest, TAMKO Glass-Seal, TAMKO Logo and Roofer Logo, Vintage and Woodgate are registered trademarks of TAMKO Building Products, Inc. AWASTAR and Marquee are trademarks of TAMKO Building Products, Inc.  
 Roll Vent, Rapid Ridge and Xtractor Vent are registered trademarks of Benjamin Obdyke Inc.

