


Panel-Loc Plus™

Product Guide

HELPFUL INFORMATION ON PANELS, TRIMS, GUTTERS AND ACCESSORIES



▲ This guide includes details for Panel-Loc and CD 2000.



***We promise to improve your business
by accurately providing quality products
right when you need them. Every time.***

Visit our website for more product information, testing, installation guides, energy ratings, warranties, photo gallery, roofing visualizer, and more.

centralstatesmfg.com

INDEX

*Information in this catalog may vary by plant location.
Please call your salesperson to verify product availability.*

Panel-Loc Plus	
Panel Codes, Fastener Spacing, Section Properties	4-5
Panel-Loc	
Panel Codes, Fastener Spacing, Section Properties	6-7
CD 2000	
Panel Codes, Fastener Spacing, Section Properties	8-9
Care and Handling, Siphon Groove	10-11
Converting Pitch to Degree	12
Square Conversions	13
Gauge and Color Codes	14
Roof Trims	15-16
Wall Trims	16-17
Soffit/Fascia	18
Gutters	19
Accessories	20-22
Sliding Doors	23-25

NOTICE: The application and detail drawings in this manual are strictly for illustration purposes and may not be applicable to all building designs or product installations. Projects should conform to local building codes. Central States Manufacturing is not responsible for the performance of the material if it is not installed correctly.

Information contained in this booklet was in effect at the time of publication and is subject to change without notice.

WARRANTIES



Warranties are available in paper format and downloadable from our website. After the job is complete, fill out a warranty with your contractor/installer details and the Central States order number. Give the warranty to the building owner to keep for their records. Optional warranty registration is available online.

Learn more at centralstatesmfg.com/warranties

PANEL-LOC PLUS

Panel-Loc Plus is available painted or bare Galvalume® in Ultra 26 ga., Prime 29 ga. and Standard 29 ga. It is also available in painted or bare galvanized Prime G90 29 ga. Ultra and Prime panels feature CentralGuard® protection and a lifetime paint warranty. Standard panels feature a 40-year paint warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

Bare (unpainted) Galvalume® and galvanized panels from Central States have an acrylic coating which eliminates using oils during manufacturing and eliminates fingerprinting and foot marking during installation.

The minimum roof slope for the ¾" Panel-Loc Plus™ is 2 ½:12. If slopes less than 3:12 are needed, International Building Code (IBC) allows a sealant tape to be used on the laps of the panel.

PANEL CODES

PANEL PROFILE	TYPE	CODE
Panel-Loc Plus™	Ultra SMP	PP6(color)
Panel-Loc Plus™	Prime SMP/Fluropon®	PP9(color)
Panel-Loc Plus™	Prime SMP G90	PP9(color)G90
Panel-Loc Plus™	Standard	PP9(color)ST
Panel-Loc Plus™	Thrifty SMP	PP6(color)TH

FASTENER SPACING

Follow the suggested fastener patterns below for interior or panel termination. Screws may be placed in either the flat or the rib. In the overlap condition, avoid using fasteners in the major rib as this may damage the siphon groove.

Fastener pattern at panel termination (Eave, endlap, valley, ridge, high eave)



Fastener pattern at interior of panel



SECTION PROPERTIES - PANEL-LOC PLUS

36" WIDE, PANEL-LOC PLUS™ PANEL

Gauge	Thickness (inches)	Weight (psf)	Yield Stress (ksi)	Top in Compression (Positive Bending)			Bottom in Compression (Negative Bending)		
				Ixx	Sxx	Ma	Ixx	Sxx	Ma
				in ⁴ /ft	in ³ /ft	in.kips/ft	in ⁴ /ft	in ³ /ft	in.kips/ft
26 ULTRA	0.0185	0.866	80.0	0.0133	0.0220	0.7913	0.0093	0.0198	0.7123
29 PRIME	0.0150	0.704	80.0	0.0110	0.0181	0.6493	0.0073	0.0160	0.5760

Section properties and allowables are calculated in accordance with 1996 AISI Specifications and 1999 AISI Supplement No. 1. I +/- is for deflection determination. S +/- is for bending determination. Ma is allowable bending moment. All values are for one foot of panel width. These loads are for panel strength. Frames, purlins, fasteners and all supports must be designed to resist all loads imposed on the panel. Allowable outward loads based on stress have been increased by 33.33% for wind uplift. Allowable loads for deflection are based on deflection limitation of span/180 or span/240. For roof panels, self weight of the panel has to be deducted from the allowable inward load to arrive at the actual "live load" carrying capacity of the panel. Minimum bearing length must be checked. Minimum deliverable bare steel thickness should not be less than 0.95 of design thickness.

THEORETICAL ALLOWABLE LIVE & WIND LOADS

SINGLE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	108.2	108.2	90.1	127.7	131.9	131.9	109.3	157.9
2.5	69.3	61.5	46.2	81.7	84.4	74.6	55.9	101.1
3	48.1	35.6	26.7	56.7	58.6	43.2	32.4	70.2
3.5	35.3	22.4	16.8	41.7	43.1	27.2	20.4	51.6
4	27.1	15.0	11.3	31.9	33.0	18.2	13.7	39.5
4.5	21.4	10.6	7.9	25.2	26.1	12.8	9.6	31.2
5	17.3	7.7	5.8	20.4	21.1	9.3	7.0	25.3
6	12.0	4.5	3.3	14.2	14.7	5.4	4.0	17.5

TWO SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	96.0	96.0	96.0	121.0	118.7	118.7	118.7	175.4
2.5	61.4	61.4	60.1	77.5	76.0	76.0	72.8	112.3
3	42.7	42.7	34.8	53.8	52.8	52.8	42.2	78.0
3.5	31.3	29.2	21.9	39.5	38.8	35.4	26.5	57.3
4	24.0	19.6	14.7	30.3	29.7	23.7	17.8	43.9
4.5	19.0	13.7	10.3	23.9	23.5	16.7	12.5	34.6
5	15.4	10.0	7.5	19.4	19.0	12.1	9.1	28.1
6	10.7	5.8	4.3	13.4	13.2	7.0	5.3	19.5

THREE OR MORE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	112.1	112.1	112.1	168.1	138.7	138.7	138.7	204.9
2.5	71.8	71.8	71.8	107.6	88.8	88.8	88.8	131.1
3	49.8	49.8	49.8	74.7	61.6	61.6	61.1	91.1
3.5	36.6	36.6	31.7	54.9	45.3	45.3	38.5	66.9
4	28.0	28.0	21.3	42.0	34.7	34.4	25.8	51.2
4.5	22.2	19.9	14.9	33.2	27.4	24.1	18.1	40.5
5	17.9	14.5	10.9	26.9	22.2	17.6	13.2	32.8
6	12.5	8.4	6.3	18.7	15.4	10.2	7.6	22.8

Theoretical allowable loads are based on uniform span lengths. LL (S) is allowable live load based on stress limitation. LL (D) is allowable live load based on deflection limitation of L/180 or L/240. WL is allowable wind load and has been increased by 33.33%.

PANEL-LOC

Panel-Loc is available in Ultra 26 gauge, Prime 29 gauge, and Standard 29 gauge; in painted or bare Galvalume®. Ultra and Prime panels feature CentralGuard® protection and a lifetime paint warranty. Standard panels feature a 40-year paint warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

Bare (unpainted) Galvalume® and galvanized panels from Central States have an acrylic coating which eliminates using oils during manufacturing and eliminates fingerprinting and foot marking during installation.


The minimum roof slope for 5/8" Panel-Loc is 3:12. If slopes less than 3:12 are needed, International Building Code (IBC) allows a sealant tape to be used on the laps of the panel.

PANEL CODES

PANEL PROFILE	TYPE	CODE
Panel-Loc™	Ultra SMP	PL6(color)
Panel-Loc™	Prime SMP/Fluropon®	PL9(color)
Panel-Loc™	Standard	PL9(color)ST
Panel-Loc™	Thrifty SMP	PL6(color)TH

FASTENER SPACING

Follow the suggested fastener patterns below for interior or panel termination. Screws may be placed in either the flat or the rib. In the overlap condition, avoid using fasteners in the major rib as this may damage the siphon groove.



SECTION PROPERTIES - PANEL-LOC

36" WIDE, PANEL-LOC™ PANEL

Gauge	Thickness (inches)	Weight (psf)	Yield Stress (ksi)	Top in Compression (Positive Bending)			Bottom in Compression (Negative Bending)		
				Ixx	Sxx	Ma	Ixx	Sxx	Ma
				in ⁴ /ft	in ³ /ft	in.kips/ft	in ⁴ /ft	in ³ /ft	in.kips/ft
26 ULTRA	0.0185	0.860	80.0	0.0097	0.0198	0.7097	0.0070	0.0189	0.677
29 PRIME	0.0150	0.698	80.0	0.0073	0.0152	0.5460	0.0053	0.0152	0.5477

Section properties and allowables are calculated in accordance with 1996 AISI Specifications and 1999 AISI Supplement No. 1. I +/- is for deflection determination. S +/- is for bending determination. Ma is allowable bending moment. All values are for one foot of panel width. These loads are for panel strength. Frames, purlins, fasteners and all supports must be designed to resist all loads imposed on the panel. Allowable outward loads based on stress have been increased by 33.33% for wind uplift. Allowable loads for deflection are based on deflection limitation of span/180 or span/240. For roof panels, self weight of the panel has to be deducted from the allowable inward load to arrive at the actual "live load" carrying capacity of the panel. Minimum bearing length must be checked. Minimum deliverable bare steel thickness should not be less than 0.95 of design thickness.

THEORETICAL ALLOWABLE LIVE & WIND LOADS

SINGLE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	91.0	80.1	60.1	121.4	118.3	105.6	79.2	150.2
2.5	58.2	41.0	30.8	77.7	75.7	54.1	40.6	96.1
3	40.4	23.7	17.8	54.0	52.6	31.3	23.5	66.8
3.5	29.7	15.0	11.2	39.6	38.6	19.7	14.8	49.1
4	22.8	10.0	7.5	30.3	29.6	13.2	9.9	37.6
4.5	18.0	7.0	5.3	24.0	23.4	9.3	7.0	29.7
5	14.6	5.1	3.8	19.4	18.9	6.8	5.1	24.0
6	10.1	3.0	2.2	13.5	13.1	3.9	2.9	16.7

TWO SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	91.3	91.3	78.2	121.0	112.9	112.9	103.1	157.3
2.5	58.4	53.4	40.1	77.5	72.3	70.4	52.8	100.7
3	40.6	30.9	23.2	53.8	50.2	40.7	30.6	69.9
3.5	29.8	19.5	14.6	39.5	36.9	25.7	19.2	51.4
4	22.8	13.0	9.8	30.3	28.2	17.2	12.9	39.3
4.5	18.0	9.2	6.9	23.9	22.3	12.1	9.1	31.1
5	14.6	6.7	5.0	19.4	18.1	8.8	6.6	25.2
6	10.1	3.9	2.9	13.4	12.5	5.1	3.8	17.5

THREE OR MORE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
2	106.6	106.6	106.6	141.1	131.9	131.9	131.9	183.8
2.5	68.2	68.2	58.1	90.5	84.4	84.4	76.5	117.6
3	47.4	44.8	33.6	62.8	58.6	58.6	44.3	81.7
3.5	34.8	28.2	21.2	46.2	43.1	37.2	27.9	60.0
4	26.7	18.9	14.2	35.3	33.0	24.9	18.7	45.9
4.5	21.1	13.3	10.0	27.9	26.1	17.5	13.1	36.3
5	17.1	9.7	7.3	22.6	21.1	12.8	9.6	29.4
6	11.8	5.6	4.2	15.7	14.7	7.4	5.5	20.4

Theoretical allowable loads are based on uniform span lengths. LL (S) is allowable live load based on stress limitation. LL (D) is allowable live load based on deflection limitation of L/180 or L/240. WL is allowable wind load and has been increased by 33.33%.

CD 2000

CD2000 is available painted or bare Galvalume® in Ultra 26 ga., Prime 29 ga. and Standard 29 ga. It is also available in painted or bare galvanized Prime G90 29 ga. Ultra and Prime panels feature CentralGuard® protection and a lifetime paint warranty. Standard panels feature a 40-year paint warranty.

CentralGuard is our specific combination of everything that goes into making the highest-quality metal panels. Choose CentralGuard for the perfect balance of fade protection, rust blocking, and dent resistance.

Bare (unpainted) Galvalume® and galvanized panels from Central States have an acrylic coating which eliminates using oils during manufacturing and eliminates fingerprinting and foot marking during installation.


The minimum roof slope for the 5/8" CD 2000 is 3:12. If slopes less than 3:12 are needed, International Building Code (IBC) allows a sealant tape to be used on the laps of the panel.

PANEL CODES

PANEL PROFILE	TYPE	CODE
CD 2000®	Ultra SMP	CD6(color)
CD 2000®	Prime SMP/Fluoropon®	CD9(color)
CD 2000®	Prime SMP G90	CD9(color)G90
CD 2000®	Standard	CD9(color)ST

FASTENER SPACING

Follow the suggested fastener patterns below for interior or panel termination. Screws should be placed in the flat. In the overlap condition, fasten away from the siphon groove so as not to damage it.



SECTION PROPERTIES - CD 2000

36" WIDE, CD 2000® PANEL

Gauge	Thickness (inches)	Weight (psf)	Yield Stress (ksi)	Top in Compression (Positive Bending)			Bottom in Compression (Negative Bending)		
				Ixx	Sxx	Ma	Ixx	Sxx	Ma
				in ⁴ /ft	in ³ /ft	in.kips/ft	in ⁴ /ft	in ³ /ft	in.kips/ft
26 ULTRA	0.0185	0.861	80.0	0.0123	0.0260	0.933	0.0103	0.0246	0.883
29 PRIME	0.0150	0.698	80.0	0.0097	0.0205	0.737	0.0077	0.0197	0.710

Section properties and allowables are calculated in accordance with North American Specification for the Design of Cold-Formed Steel Structural Members (2012 Edition). I +/- is for deflection determination. S +/- is for bending determination. Ma is allowable bending moment. All values are for one foot of panel width. These loads are for panel strength. Frames, purlins, fasteners and all supports must be designed to resist all loads imposed on the panel. Allowable load based on stress is the smallest load due to bending, shear, distortional buckling and combined bending and shear. Allowable uplift load based on stress have not been increased 33.33% for wind uplift. For roof panels, self weight of the panel has to be deducted from the allowable inward load to arrive at the actual 'live load' carrying capacity of the panel. Minimum bearing length must be checked. Minimum deliverable bare steel thickness should not be less than 0.95 of design thickness.

THEORETICAL ALLOWABLE LIVE & WIND LOADS

SINGLE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
1.5	155.9	155.9	155.9	210.4	207.2	207.2	207.2	261.7
1.75	114.5	114.5	114.5	154.6	152.2	152.2	150.9	192.3
2	87.7	87.7	79.2	118.3	116.5	116.5	101.1	147.2
2.5	56.1	54.1	40.6	75.7	74.6	69.0	51.7	94.2
3	39.0	31.3	23.5	52.6	51.8	39.9	29.9	65.4
4	21.9	13.2	9.9	29.6	29.1	16.8	12.6	36.8
4.5	17.3	9.3	7.0	23.4	23.0	11.8	8.9	29.1
4	14.0	6.8	5.1	18.9	18.6	8.6	6.5	23.6

TWO SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
1.5	196.5	196.5	196.5	155.9	244.0	244.0	244.0	207.2
1.75	146.8	146.8	146.8	114.5	182.4	182.4	182.4	152.2
2	113.7	113.7	113.7	87.7	141.3	141.3	141.3	116.5
2.5	73.8	73.8	73.8	56.1	91.8	91.8	74.6	74.6
3	51.7	51.7	51.7	39.0	64.2	64.2	51.8	51.8
4	29.3	29.3	23.8	21.9	36.4	30.4	29.1	29.1
4.5	23.2	22.3	16.7	17.3	28.8	28.5	21.4	23.0
5	18.8	16.3	12.2	14.0	23.4	20.8	15.6	18.6

THREE OR MORE SPAN CONDITION

Span (feet)	29 Gauge & 80 ksi				26 Gauge & 80 ksi			
	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)	LL (S)(psf)	LL (D) L/180(psf)	LL (D) L/240(psf)	WL(psf)
1	225.2	225.2	225.2	181.9	279.5	279.5	279.5	241.8
1.5	169.1	169.1	169.1	133.7	210.0	210.0	210.0	177.7
1.75	131.3	131.3	131.3	102.3	163.2	163.2	163.2	136.0
2	85.5	85.5	76.5	65.5	106.3	106.3	106.3	87.0
3	60.0	59.1	44.3	45.5	74.6	74.6	74.6	60.5
4	34.1	24.9	18.7	25.6	42.4	42.4	42.4	34.0
4.5	27.0	17.5	13.1	20.2	33.6	22.3	16.7	26.9
5	21.9	12.8	9.6	16.4	27.3	16.3	12.2	21.8

Theoretical allowable loads are based on uniform span lengths. LL (S) is allowable live load based on stress limitation. LL (D) is allowable live load based on deflection limitation of L/180 or L/240. WL is allowable wind load.

DELIVERY

Deliveries will be made using a 65' tractor/trailer weighing approximately 80,000 lbs. It is imperative that all delivery locations be accessible by a vehicle of this size. Our drivers have the authority to refuse delivery to any location they see as unsafe or inaccessible. The customer is responsible

for any charges incurred if truck is detained for any reason. The customer is responsible for unloading all trucks. Any damage that occurs at this point is the customer's responsibility. There must be equipment available to unload the truck. Moffett deliveries require at least one person to assist with unloading.

CARE AND HANDLING

STAGE

Galvalume® steel panels have a good service life when exposed to normal weather conditions; however, to protect the appearance of panels and trims from damage, there are a few simple precautions that can be taken. The steel panels are subject to stain when water sits upon, or becomes trapped between the sheets. If the Galvalume® panels are to be stored for any period of time, they should be stored only in a dry place, preferably under a roof. Stand panels on end and fan them out at the bottom to provide air circulation and moisture run off. If space does not allow this, the panels should be separated, blocked off of the floor at least 12 inches to allow air flow, and stored at an incline to encourage drainage. The panels should then be covered, yet still have good air flow through the sheets to prevent condensation. Do not use a plastic cover, as this may cause the panels to sweat or condensation to occur.

STORAGE

Failure to follow these steps may result in wet storage stains and premature rusting. The manufacturers warranty will be void at this time, and the manufacturer will not be responsible.

HANDLING

When unloading panels, extreme caution must be employed. Care needs to be used when unloading panels with a forklift. Panel edges and underside paint may become damaged if the forklift driver does not use caution. Once at the job site, care must be taken in order to protect the painted surface. When unbundling the panels, never drag them across the surface of one another. This may cause scratches across the underneath panels. It is recommended that the panels be "rolled" off the top of the bundle to prevent scratching. Never lift panels by the ends, instead lift the panels longitudinally and carry vertically.

Panel edges are very sharp, therefore, safety equipment should be worn by all workers handling the material.

CARE AND HANDLING

CUTTING

A portable field shear is the ideal method for cutting panels. Nibblers or a power shear may also be used. Although we do not recommend it, if you decide to cut with a saw, it is very important that the panels be turned upside down during cutting so that hot shavings do not come in contact with the painted surface. Make sure all adjacent panels are covered so that shavings are not imbedded in these panels. If metal shavings become imbedded in the paint surface, they will quickly rust. To avoid this, panels should be thoroughly wiped of all filings on both sides of the panel. Failure to comply with the recommended cutting procedures releases the manufacturer of any responsibility.

Shavings created by saw cutting or drilling may cause the panel to rust and will void warranties in affected areas.




DRILLING

Panels should not be drilled while stacked. This will cause shavings that will become imbedded in the paint surface.

SIPHON GROOVE



Panel-Loc Plus, Panel-Loc, and CD 2000 have two vertical edges, the overlap and the sidelap. The sidelap edge has a specific bend in the last major rib, called a siphon groove. When the overlap edge is installed on top of the sidelap edge, it creates an air gap that prevents water from wicking under the panel. Panels should be installed with the overlap facing away from the prevailing wind.

Do not damage the siphon groove by using a stitch screw on top of the major rib or clog it with butyl tape.



CONVERTING PITCH TO DEGREE

Use these charts to calculate degrees when designing custom trim.
Please specify pitch when ordering.



SINGLE SLOPE PITCHES

Fascia, Eave, Endwall, Tie-In, Gutter

DOUBLE SLOPE PITCHES

Hip, Valley



RIDGE CAP

1:12 PITCH	2:12 PITCH	3:12 PITCH	4:12 PITCH	5:12 PITCH	6:12 PITCH	7:12 PITCH	8:12 PITCH	9:12 PITCH	10:12 PITCH	11:12 PITCH	12:12 PITCH
94°	99°	104°	108°	112°	116°	120°	123°	126°	129°	132°	135°
173°	167°	160°	154°	148°	143°	138°	134°	130°	126°	123°	120°
170°	161°	152°	143°	135°	127°	120°	113°	106°	100°	95°	90°

TRANSITION TRIM

Find the box that intersects your lower and upper roof pitches.

If the intersection lands in the gray area, select a Lower Transition trim.



LOWER ROOF PITCH (INCHES OF RISE OVER 12" OF RUN)

	1:12 PITCH	2:12 PITCH	3:12 PITCH	4:12 PITCH	5:12 PITCH	6:12 PITCH	7:12 PITCH	8:12 PITCH	9:12 PITCH	10:12 PITCH	11:12 PITCH	12:12 PITCH	13:12 PITCH	14:12 PITCH	15:12 PITCH	16:12 PITCH	17:12 PITCH	18:12 PITCH
1:12 PITCH		175°	171°	166°	162°	158°	155°	151°	148°	145°	142°	140°	137°	135°	133°	132°	130°	128°
2:12 PITCH	175°		175°	171°	167°	163°	159°	156°	153°	150°	147°	144°	142°	140°	138°	136°	135°	133°
3:12 PITCH	171°	175°		176°	171°	167°	164°	160°	157°	154°	152°	149°	147°	145°	143°	141°	139°	138°
4:12 PITCH	166°	171°	176°		176°	172°	168°	165°	162°	159°	156°	153°	151°	149°	147°	145°	144°	142°
5:12 PITCH	162°	167°	171°	176°		176°	172°	169°	166°	163°	160°	158°	155°	153°	151°	149°	148°	146°
6:12 PITCH	158°	163°	167°	172°	176°		176°	173°	170°	167°	164°	162°	159°	157°	155°	153°	152°	150°
7:12 PITCH	155°	159°	164°	168°	172°	176°		177°	173°	170°	168°	165°	163°	161°	159°	157°	155°	154°
8:12 PITCH	151°	156°	160°	165°	169°	173°	177°		177°	174°	171°	169°	166°	164°	162°	161°	159°	157°
9:12 PITCH	148°	153°	157°	162°	166°	170°	173°	177°		177°	174°	172°	170°	167°	166°	164°	162°	161°
10:12 PITCH	145°	150°	154°	159°	163°	167°	170°	174°	177°		177°	175°	173°	170°	168°	167°	165°	163°
11:12 PITCH	142°	147°	152°	156°	160°	164°	168°	171°	174°	177°		178°	175°	173°	171°	169°	168°	166°
12:12 PITCH	140°	144°	149°	153°	158°	162°	165°	169°	172°	175°	178°		178°	176°	174°	172°	170°	169°

SQUARE CONVERSIONS

For 26 ga. and 29 ga. low rib panels there are 2 formulas; one for panels measured in inches and one for panels measured in feet. While the actual panel width is 38", there will only be 36" of coverage per panel. Squares are figured based on actual width. One square is equal to a panel 31.579 feet long. One square of metal will give you approximately 94.5 square feet of coverage. One square is equal to 14,400 square inches.

EXAMPLE USING INCHES:

38 (or width in inches) multiplied by length in inches
multiplied by # of pieces divided by 14,400

Number of panels = 12 $\frac{38" \times 144" \times 12}{14,400}$ equals 4.56 squares of metal
Panel width = 38"
Panel length = 144"
Square inches = 14,400

EXAMPLE USING FEET:

length in feet multiplied by # of pieces
divided by 31.579*

Number of panels = 12 $\frac{12 \times 12}{31.579}$ equals 4.56 squares of metal
Panel width = 38"
Panel length = 12'

*For 26ga. Thrifty Panel-Loc Plus or Panel-Loc, use 31.373 in place of 31.579.

COMMON RAFTER LENGTHS (PEAK TO SIDEWALL)

Running Feet	1:12 Pitch	2:12 Pitch	3:12 Pitch	4:12 Pitch	5:12 Pitch	6:12 Pitch
1	1' 0"	1' 1/8"	1' 3/8"	1' 5/8"	1' 1"	1' 1-3/8"
2	2' 1/8"	2' 3/8"	2' 3/4"	2' 1-1/4"	2' 2"	2' 2-7/8"
3	3' 1/8"	3' 1/2"	3' 1-1/8"	3' 2"	3' 3"	3' 4-1/4"
4	4' 1/8"	4' 5/8"	4' 1-1/2"	4' 2-5/8"	4' 4"	4' 5/8"
5	5' 1/4"	5' 7/8"	5' 1-7/8"	5' 3-1/4"	5' 5"	5' 7-1/8"
6	6' 1/4"	6' 1"	6' 2-1/4"	6' 3-7/8"	6' 6"	6' 8-1/2"
7	7' 1/4"	7' 1-1/8"	7' 2-5/8"	7' 4-1/2"	7' 7"	7' 9-7/8"
8	8' 3/8"	8' 1-3/8"	8' 3"	8' 5-1/4"	8' 8"	8' 11-3/8"
9	9' 3/8"	9' 1-1/2"	9' 3-3/8"	9' 5-7/8"	9' 9"	10' 3/4"
10	10' 3/8"	10' 1-5/8"	10' 3-3/4"	10' 6-1/2"	10' 10"	11' 2-1/8"
11	11' 1/2"	11' 1-7/8"	11' 4-1/8"	11' 7-1/8"	11' 11"	12' 3-5/8"
12	12' 1/2"	12' 2"	12' 4-3/8"	12' 7-3/4"	13' 0"	13' 5"
13	13' 1/2"	13' 2-1/8"	13' 4-3/4"	13' 8-1/2"	14' 1"	14' 6-3/8"
14	14' 5/8"	14' 2-3/8"	14' 8-1/8"	14' 9-1/8"	15' 2"	15' 7-7/8"
15	15' 5/8"	15' 2-1/2"	15' 5-1/2"	15' 9-3/4"	16' 3"	16' 9-1/4"
16	16' 5/8"	16' 2-5/8"	16' 5-7/8"	16' 10-3/8"	17' 4"	17' 10-5/8"
17	17' 5/8"	17' 2-7/8"	17' 6-1/4"	17' 11"	18' 5"	19' 1/8"
18	18' 3/4"	18' 3"	18' 6-5/8"	18' 11-5/8"	19' 6"	20' 1-1/2"
19	19' 3/4"	19' 3-1/8"	19' 7"	20' 3/8"	20' 7"	21' 2-7/8"
20	20' 7/8"	20' 3-3/8"	20' 7-3/8"	21' 1"	21' 8"	22' 4-3/8"
21	21' 7/8"	21' 3-1/2"	21' 7-3/4"	22' 1-5/8"	22' 9"	23' 5-3/4"
22	22' 7/8"	22' 3-5/8"	22' 8-1/8"	23' 2-1/4"	23' 10"	24' 7-1/8"
23	23' 1"	23' 3-3/4"	23' 8-1/2"	24' 3"	24' 11"	25' 8-5/8"
24	24' 1"	24' 4"	24' 8-7/8"	25' 3-5/8"	26' 0"	26' 10"
25	25' 1"	25' 4-1/8"	25' 9-1/4"	26' 4-1/4"	27' 1"	27' 11-3/8"
26	26' 1-1/8"	26' 4-1/4"	26' 9-1/2"	27' 5"	28' 2"	29' 3/4"
27	27' 1-1/8"	27' 4-1/2"	27' 9-7/8"	28' 5-5/8"	29' 3"	30' 2-1/4"
28	28' 1-1/8"	28' 4-3/4"	28' 10-1/4"	29' 6-1/4"	30' 4"	31' 3-3/4"
29	29' 1-1/4"	29' 4-7/8"	29' 10-5/8"	30' 6-7/8"	31' 5"	32' 5-1/8"
30	30' 1-1/4"	30' 5"	30' 11"	31' 7-1/2"	32' 6"	33' 6-1/2"
31	31' 1-3/8"	31' 5-1/8"	31' 11-3/8"	32' 8-1/8"	33' 7"	34' 7-7/8"
32	32' 1-3/8"	32' 5-1/4"	32' 11-3/4"	33' 8-3/4"	34' 8"	35' 9-1/4"
33	33' 1-1/2"	33' 5-1/2"	34' 1/8"	34' 9-3/8"	35' 9"	36' 10-3/4"
34	34' 1-1/2"	34' 5-3/4"	35' 1/2"	35' 10"	36' 10"	38' 1/4"
35	35' 1-1/2"	35' 5-7/8"	36' 7/8"	36' 10-5/8"	37' 11"	39' 1-5/8"

HOW TO ORDER TRIM


STEP 1:

In CentralLink™, start by entering the Item ID.

Item ID is made of the **TRIM CODE**, a **GAUGE CODE**, and a **COLOR CODE**.

The TRIM CODE can be found with each drawing next to the trim's name.

The GAUGE CODE and COLOR CODES are found below.



EXAMPLE: Ridge Cap, 26 gauge, Rustic

RCP **6** **RR**
TRIM CODE GAUGE CODE COLOR CODE

Enter Item ID

Description: 26, Rustic, Ridge Cap

Pieces

Feet

Inches

CentralLink order screen

STEP 2:

Then type the number of pieces you need along with the length in feet and inches.

GAUGE CODES

GAUGE	CODE
26	6
29	9

COLOR CODES

SMP	PANEL GAUGE	TRIM GAUGE	CODE	TEXTURE SMP	PANEL GAUGE	TRIM GAUGE	CODE
Alamo	29/26	29	AW	Basil*	29	26	BA
Black	29/26	29	BK	Cream*	29	26	CE
Brilliant	29/26	29/26	BI	Granite*	29	26	GT
Brown	29/26	29/26	BR	Linen*	29	26	LN
Burgundy	29/26	29/26	BG	Mineral*	29	26	MI
Burnished Slate	29/26	29/26	BS	Onyx*	29	26	OX
Charcoal	29/26	29/26	CH	Roma*	29	26	RM
Colony	29	26	CG	Sienna*	29	26	SI
Copper Metallic**	29	29	CM	Suede*	29	26	SE
Crimson	29/26	29/26	CR	Sumatra*	29	26	SU
Desert	29	26	DS				
Forest	29/26	29/26	DG				
Gallery	29/26	29/26	GB				
Galvalume®	29/26	29/26	GL				
Galvanized	29	29	ZN				
Gray	29/26	29/26	GA				
Hawaiian		26	HB				
Hunter	29/26	29/26	GR				
Ivory	29	29	IV				
Light Stone	29/26	29/26	LS				
Ocean	29/26	29	OB				
Pewter	29	26	PG				
Polar		26	PW				
Rustic	29/26	29/26	RR				
Tan	29/26	29/26	TN				
Taupe	29/26	29/26	TA				

* Longer lead times may apply. ** Copper Metallic is Fluropon®.
Galvalume® is a registered trademark of BIEC International, Inc.


ROOF TRIMS

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 14 for gauge and color codes.

TRANSITION TRIMS - Specify pitch.


GAMBREL TRIM UPPER

GTU - Girth 10.25"




GAMBREL TRIM LOWER

GTL - Girth 10.25"




GAMBREL TRIM LOWER

GTL2 - Girth 14.5"




UNIVERSAL SIDEWALL

SF1 - Girth 9.25"




UNIVERSAL ENDWALL

EF - Girth 12.5"



ENDWALL FLASHING

EFF - Girth 12"




WALL TRIMS

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 14 for gauge and color codes.


INSIDE CORNER

IC1 - Girth 13"




J-TRIM

JT - Girth 4.8125"



WINDOW DRIP CAP

WC - Girth 3.75"



FLAT SHEET

FS9 - 29 gauge. Girth 43"


FS6 - 26 gauge. Girth 41.5625"



10 sheets or fewer will be packaged in a roll.
Additional pallet charge on orders of 10 or more.


RAKE & CORNER

COR - Girth 13"




MINI CORNER

MCRN - Girth 9.5"



SQUARE BASE


SBA - Girth 5"



RAT GUARD

RG - Girth 4.75"

RG1 - Girth 5.5625"



WALL TRIMS

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 14 for gauge and color codes.

ANGLE


POST TRIM

SA312 - Girth 5.5"

SA512 - Girth 7.5"

SA7 - Girth 9"

SA712 - Girth 9.5"




For hem on other leg, refer to Residential Fascia Trim.

INSIDE ANGLE

IA112 - Girth 4"


IA2X2 - Girth 5"

IA3X3 - Girth 7"



DOUBLE ANGLE


DA1 - Girth 3.5"



Use with wainscot.

WIDE DOUBLE ANGLE

DA2 - Girth 4.5"




Use with wainscot.

SINGLE ANGLE

SA112 - Girth 4"

SA2X2 - Girth 5"


SA3X3 - Girth 7"



FRAMED OPENING TRIMS


OVERHEAD DOOR JAMB 7 1/8"

OHDJ7 - Girth 12.5"



OVERHEAD DOOR JAMB 7 7/8"


OHDJWD7 - Girth 12"



With drip edge.


OVERHEAD DOOR JAMB 9 1/4"

OHDJ9 - Girth 14.25"



OVERHEAD DOOR JAMB 9 7/8"


OHDJWD9 - Girth 14"



With drip edge.


DOOR POST TRIM

DJ8 - Girth 12.5"




DOOR POST TRIM

DJ9 - Girth 13.5"



DOOR EDGE


DJ10 - Girth 11.25"



SLIDING DOOR TRIMS

TRACK DOOR JAMB


TDJT - Girth 14.375"



SQUARE TRACK COVER NATL

NTC - Girth 12.1875"


NT2 - Girth 9.125"



ROUND TRACK COVER

CTC - Girth 13"

DC1 - Girth 17.625"




SOFFIT/FASCIA

Unless otherwise noted, trims come in 29 or 26 gauge, and all angles are 90° or 45°. See page 14 for gauge and color codes.

ALUMINUM SOFFIT

VS(color) - Vented


SS(color) - Solid



Length 12'.

BEADED FASCIA

BFT9(color)102 - Girth 8.25"




29 gauge only. Length 10'2".

RESIDENTIAL FASCIA TRIM

RFT312 - Girth 5.5"


RFT512 - Girth 7.5"

RFT712 - Girth 9.25"




GABLE BASE SOFFIT

GB1 - Girth 20.25"



SOFFIT F ADAPTOR


SFA - Girth 4.75"



Random color. Use to make F&J Assembly.


J-TRIM

JT - Girth 4.8125"




Use to make F&J Assembly.

F&J ASSEMBLY - (SFA & JT)




SOFFIT J-TRIM

SJT - Girth 3.625"




SOFFIT F&J

SFJ - Girth 9.375"



PANEL-LOC PLUS F&J


PFJ - Girth 9.125"



F CHANNEL



FC12 - Girth 7.5"

FC38 - Girth 7.375"



FC12


FC38




GUTTERS

K5 Gutters are not available in Galvalume, Hawaiian, or Polar.

K5 GUTTER
K5G9(color)206 - Length 20'6"



FLUTED DOWNSPOUT
K6DS9(color)100 - Length 10'




Sold separately or 15 per box.

DOWNSPOUT STRAP
K6DSS(color)




Sold separately or 100 per box.

DOWNSPOUT ELBOW
K6EA9(color) - Style A, 4" x 3"
K6EB9(color) - Style B, 3" x 4"




Sold separately or 20 per box. Style A shown.

K5 GUTTER END CAP
K5ECR(color) - Right
K5ECL(color) - Left




Specify right or left hand.

CORNER BOXES
K5GISQCR - Inside
K5GOSQCR - Outside




White only.

CONCEALED FASCIA BRACKET
K5GCFZ




Sold separately or 100 per box.

DOWNSPOUT OUTLET
K5GOOFZ - Fits inside K5 Gutter




Sold separately or 20 per box.



ACCESSORIES

BUTYL TAPE



PART #	LENGTH	WIDTH	THICKNESS	ROLLS PER BOX
BT3/8	45'	3/8"	3/32"	40
<i>Recommended for Panel-Loc Plus.</i>				
BTR	40'	7/8"	3/16"	10
BTL	45'	3/4"	3/32"	24

*Install between fastener and exposed edge.
Rolls per box may vary by location and vendor. Check with your sales person for details.*

SEALANT



PART #	SIZE	COLOR
GEO(color)	10.3 oz. tube	clear, gray, white
MRS10CLEAR	10.3 oz. tube	clear


TOUCH UP PAINT

TP(color) - SMP, 0.6 oz. bottle w/brush.



DOOR SET - With steel jamb.

3068DR - 38" x 81 3/16"
KNOB



Door knobs sold separately.

FASTENERS

Fastener color availability may vary by location, contact your sales consultant for details. Order fasteners in increments of 250 pieces.

TYPE	PART #	LENGTH	DIAMETER	HEAD	COLOR	#BAG
METAL/WOOD	1(color)MW	1"	#10	1/4" Hex	all	250
METAL/WOOD	112(color)MW	1 1/2"	#10	1/4" Hex	all	250
METAL/WOOD	2(color)MW	2"	#10	1/4" Hex	all	250
METAL/WOOD	212(color)MW	2 1/2"	#10	1/4" Hex	all	250
METAL/WOOD	3(color)MW	3"	#10	1/4" Hex	all	250
METAL/WOOD STITCH	34(color)ST	3/4"	#12	1/4" Hex	all	250
METAL/METAL	34(color)MM	3/4"	#12	5/16" Hex	all	250
METAL/METAL	114(color)MM	1 1/4"	#12	5/16" Hex	all	250
METAL/METAL	2ZMM	2"	#12	5/16" Hex	galvanized	250
METAL/METAL LAP	78(color)LAP	7/8"	#14	5/16" Hex	all	250
LOW PROFILE WAFER HEAD	1WFAST	1"	#10	#2 Square drive	galvanized	250

ACCESSORIES

CLOSURES

- Sold separately or by the box. Longer lead times for Panel-Loc closures.



Panel-Loc Plus outside closure shown.



Panel-Loc Plus inside closure shown.



Panel-Loc Plus closure vent shown.

INSIDE CLOSURE - Length - 3': 100 per box.

PPCLIN	Panel-Loc Plus
PPCLINGLUE	Panel-Loc Plus - with adhesive
PLCLIN	Panel-Loc
PLCLINGLUE	Panel-Loc - with adhesive
CDCLIN	CD 2000
CDCLINGLUE	CD 2000 - with adhesive

OUTSIDE CLOSURE - Length - 3': 100 per box.

PPCLOUT	Panel-Loc Plus
PPCLOUTGLUE	Panel-Loc Plus - with adhesive
PLCLOUT	Panel-Loc
PLCLOUTGLUE	Panel-Loc - with adhesive
CDCLOUT	CD 2000
CDCLOUTGLUE	CD 2000 - with adhesive


CLOSURE VENT - Length - 3': 25 rolls per box.

PPCLV	Panel-Loc Plus
PLCLV	Panel-Loc
CDCLV	CD 2000

Closure is 1 3/8" tall and may require longer screws for installation.
Item may vary from sample shown.

PROFILE RIDGE VENT


PPVENT - Net free area 23.3sq.in/ft



Length - 100'; Width - 3"; Thickness - 1"

CONTINUOUS RIDGE VENT

RLW - Available white only.



Length - 10'

RETRO-EASE RETROEASE




Length 300'

GRAYFLEX
GRAYFLEX-6 - 24-rolls per box.
For use with hips and valleys.




Length 20'; Width 1"; Thickness 1"

UNIVERSAL POLYFOAM
POLYG - With glue. 10-rolls per box.



Length 25'; Width 1 1/2"; Thickness 1 1/2"

FLEXOVENT
FLEXOVENT - (2) 10' rolls per box.




Length 10'; Width 3"; Thickness 1 1/2"

ACCESSORIES

SKYLIGHTS

- For best results, use approved sealant (MRS10SKY) and washer (118WASHER). Skylights should be predrilled. Longer lead times for Panel-Loc skylights.



Panel-Loc Plus - Clear Polycarbonate

PPSKYPCC8 - Length 8'.

PPSKYPCC10 - Length 10'.

PPSKYPCC12 - Length 12'.

Panel-Loc Plus - White Polycarbonate

PPSKYPCW8 - Length 8'.

PPSKYPCW10 - Length 10'.

PPSKYPCW12 - Length 12'.

Panel-Loc - Fiberglass 5 oz. sqft weight

PLSKY12 - Length 12'.

CD 2000 - Clear Polycarbonate

CDSKYPCC12 - Length 12'.



Skylight Washer - White.

118WASHER - 1/8" outside diameter, 1/4" inside diameter

100 per bag. Do not overtighten to allow for expansion of material.



Skylight Sealant - Clear.


MRS10SKY 10.3 oz. tube

Approved for skylight use.

MASTER PIPE FLASHING

- Install in a diamond shape and not parallel to the rib.

Square - Max temperature 250°.



MPF - Pipe size .25" to 5.75"

MPF2 - Pipe size .875" to 4"

MPF4 - Pipe size 2.75" to 7"

MPF5 - Pipe size 4" to 8.25"

MPF6 - Pipe size 4.75" to 10"

MPF7 - Pipe size 5.5" to 11.5"

MPF8 - Pipe size 6.75" to 13.5"

MPF9 - Pipe size 9.5" to 20.5"

Silicone - Orange, high temp max 500°.


4SMPF - Pipe size 2.75" to 7"

6SMPF - Pipe size 4.75" to 10"

8SMPF - Pipe size 6.75" to 13.5"

10SMPF - Pipe size 12" to 28.5"

Square with zipper - Max temperature 250°.



MPF1ZIP - Pipe size .5" - 4"

MPF2ZIP - Pipe size 4" - 9.25"

SLIDING DOOR

To figure a sliding door you will need to know:

1. What is the door opening width?
2. What is the door height?
3. Is it a single or double door?
4. Do they want track cover?
5. Do they want to attach the door using a side mount or top mount hanger?

MINIMUM COMPONENTS NEEDED

Door Track – You need twice the footage for the door opening. A 10' door will need 20' of track.

Splice Collars – You need these to connect the track sections together.

Trolleys – 1 Pair per door is usually enough.

Track Hangers – Either side mount or top mount (with or without cover supports). Divide the total track footage in half and add one.

EXTRA COMPONENTS

End caps – One pair per each door opening.

Vertical Rails – If it is a single door, two male vertical rails are needed. Length is determined by the door height. If it is a double door, three male rails and one female vertical rail are needed.

Latches – Used to snug the door tight to the jambs when closed.


Center Bar or Chain Latch – Use either one on a double door to close the door together at the center.

Door Pulls – One needed per door.

Door Stops – Used to stop the door from sliding too far.

Bottom guide rail system – Either use the aluminum bottom rail for guide along with the bottom guide rail, or use the aluminum bottom rail for stayroller along with a stayroller. To figure amount of guide needed, take the length closest to 60% of the door width.

Track Cover – Used to cover the sliding door track. Round track cover is used with a round track system. National track cover is used with a square track system. You need to make sure to use the track hangers with cover supports if track cover is used.




EXAMPLE

These are the parts needed for a 20' wide door opening, with double doors, 14' tall with track cover, using side mount brackets.

- 10STRK – 4
- SPLCLP – 3
- ENDCAP – 2
- TRLYWRB – 2
- SMB/CS – 21
- DRPUL – 2
- LTCH – 2
- CTRCHLK – 1
- 14VRTRL – 3
- 14VRTRWH – 1
- 10BRL – 2
- 6BGRL – 2
- CGWHD – 1
- DRSTPVWC – 2
- CTC – 4


SLIDING DOOR

SLOTTED TRACK



STRK80 - Length 8'
STRK100 - Length 10'
STRK120 - Length 12'


SPLICE CLIP
SPLCLP




TRACK END CAPS
ENDCAPS - Sold in pairs.




TRACK MOUNTING BRACKETS



TOP MOUNT BRACKET
TMB
TMB/CS - with cover support.




DOUBLE SIDE MOUNT BRACKET
DTB
DTB/CS - with cover support.




SIDE MOUNT BRACKET
SMB
SMB/CS - with cover support.

VERTICAL ALUMINUM RAILS




VRTRL100 - 10' AV Male
VRTRL120 - 12' AV Male
VRTRL140 - 14' AV Male
VRTRL160 - 16' AV Male



VRTWH100 - 10' HV Female
VRTWH120 - 12' HV Female
VRTWH140 - 14' HV Female
VRTWH160 - 16' HV Female


DOOR GUIDE SYSTEM

These three components are designed to go together as a guide system. Be sure to also order a Heavy Duty Stay Roller.




CENTER DOOR GUIDE
CGWHD

BOTTOM RAIL - FOR CENTER DOOR GUIDE



BRL80 - Length 8'
BRL100 - Length 10'
BRL120 - Length 12'
BRL140 - Length 14'
BRL160 - Length 16'



BOTTOM RAIL GUIDE


BGRL60 - Length 6'
BGRL80 - Length 8'
BGRL100 - Length 10'

SLIDING DOOR


HEAVY DUTY STAY ROLLER

These two components are designed to go together as a guide system.

STYRLLR




ABRL12 - Length 12'.



Aluminum bottom rail for stay roller.

TROLLYS - 2 per bag

PLATE TROLLY
DSRLLRWRB - With roller bearing



Includes endcaps.

9.5" BOLT TROLLY
TRLYWRB - With roller bearing




SLIDING DOOR ACCESSORIES

DOOR PULL
DRPUL - Available in white only.




INSIDE DOOR STOP
IDS




HEAVY DUTY DOOR STOP
DRSTP



ADJUSTABLE DOOR STOP
DRSTPWVC




JAMB LATCH (cam latch)
LTCH



CENTER CHAIN LOCK
CTRCHLK



CENTER BAR LOCK
CTRBAR



[illegible]



Right.
On Time.
Every Time.

centralstatesmfg.com